


78L08

3-Terminal positive voltage regulator

Features

- Internal short-circuit current limiting
- Internal thermal overload protection
- Maximum output current of 100 mA ($T_j = 25^\circ\text{C}$)



1. Output 2. Common 3. Input
TO-92 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Input Voltage	V_{IN}	35	V
Power Dissipation	P_{tot}	625	mW
Operating Temperature	T_{opr}	- 30 to + 75	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

Electrical Characteristics (Unless otherwise specified, $V_{IN} = 14\text{ V}$, $I_{OUT} = 40\text{ mA}$, $C_{IN} = 0.33\text{ }\mu\text{F}$, $C_{OUT} = 0.1\text{ }\mu\text{F}$, $T_j = 25^\circ\text{C}$)

Parameter	Symbol	Min.	Typ.	Max.	Unit
Output Voltage	V_{OUT}	7.7	8	8.3	V
Input Regulation $10.5\text{ V} \leq V_{IN} \leq 23\text{ V}$ $11\text{ V} \leq V_{IN} \leq 23\text{ V}$	Reg. line	- -	20 12	175 125	mV
Load Regulation $1\text{ mA} \leq I_{OUT} \leq 100\text{ mA}$ $1\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$	Reg. load	- -	15 7	80 40	mV
Output Voltage $10.5\text{ V} \leq V_{IN} \leq 23\text{ V}$ $1\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$	V_{OUT}	7.6	-	8.4	V
Output Voltage $V_{IN} = 14\text{ V}$ $1\text{ mA} \leq I_{OUT} \leq 70\text{ mA}$	V_{OUT}	7.6	-	8.4	V
Quiescent Current	I_B	-	3.1	6.5	mA
Quiescent Current Change $11\text{ V} \leq V_{IN} \leq 23\text{ V}$ $1\text{ mA} \leq I_{OUT} \leq 40\text{ mA}$	ΔI_B	- -	- -	1.5 0.1	mA
Output Noise Voltage at $T_a = 25^\circ\text{C}$, $10\text{ Hz} \leq f \leq 100\text{ KHz}$	V_{NO}	-	60	-	μV
Ripple Rejection at $f = 120\text{ Hz}$, $12\text{ V} \leq V_{IN} \leq 23\text{ V}$, $T_j = 25^\circ\text{C}$	RR	37	45	-	dB
Dropout Voltage at $T_j = 25^\circ\text{C}$	$ V_{IN} - V_{OUT} $	-	1.7	-	V
Average Temperature Coefficient of Output Voltage at $I_{OUT} = 5\text{ mA}$	TC_{VO}	-	-0.8	-	mV/ $^\circ\text{C}$

